

Geronimo Bill of Materials

The following list of materials is intended to be a general guide only. Before ordering any materials, the text and plans should be checked for possible options. All lumber listed as 1" stock is to be standard "lumberyard four-quarter" material which when finished may vary to somewhat less or slightly more than 3/4" in thickness, unless specified as NET. All widths are NET and all lengths allow for cutting to fit. Grouping lumber and purchasing random-random material to resaw to the required size will result in considerable savings. All lumber used should be first grade free from shakes and knots. Although oak (white oak), spruce (Sitka), and mahogany (dark red Philippine type) are called out in the listing, lumber typical to the locale and of similar types and weights may be substituted. All plywood (PW) is to be marine (MAR) or exterior (EXT) grade. The marine-type is preferable as the inner cores are solid and thus the panel has more structural integrity. Douglas-fir (DF) is satisfactory with the quality of the exposed faces of the veneer being designated by the letters "A" or "B". The "AA" grade panels are always preferable, however, "AB" grade is acceptable. All plywood should be a minimum of three plies. All fastenings should be bronze or hot dipped galvanized ferrous metal. Brass fastenings are not advised nor are the electroplated screws commonly sold in hardware stores. All screws are to be of the flat head type intended for wood. All nails are of the ring-type nail common to boat construction. Unless otherwise specified, all wood-to-wood joints are to be glued with a waterproof or highly water resistant glue such as plastic resin, resorcinol, epoxy, or other equivalent type used per the manufacturer's instructions regarding temperature, clamping requirements, curing time, and mixing method.

CHECK ALL SIZES TO THE WORK PRIOR TO CUTTING. Abbreviations used are: Mahog = mahogany; SP = spruce; DF = Douglas-fir; PW=plywood; Ext=exterior; MAR=marine.

ITEM	MATERIAL	NO. PCS.	SIZE
LUMBER:			
*Frames	Oak, Mahog or SP	50 Bd. Ft. Random-widths & lengths of 1" material	

Keel	Oak, Mahog or SP	1	1" x 4" x 12'
Chine Log	Oak, Mahog or SP	2	1"(net) x 2" x 16'
Sheer Clamp	Oak, Mahog or SP	4	5/8" x 1-1/4" x 17'
Battens, Bottom	Oak, Mahog or SP	2	1" x 3" x 12'
Battens, Bottom	Oak, Mahog or SP	2	1" x 3" x 10'
Skeg	Oak, Mahog or SP	1	1-1/4" x 2" x 10'
Spray Rail (Optional)	Oak, Mahog or SP	2	1" x 1-1/4" x 16'
Stem Cap Strip (Optional)	Oak, Mahog or SP	2	1" x 1-1/4" x 7'
Carlings	Oak, Mahog or SP	2	1" x 4" x 12'
Coamings	Oak, Mahog or SP	2	1" x 7" x 12'
Intermediate Deck Beams	Oak, Mahog or SP	1	1" x 6" x 5'

Hatch Framing	Oak, Mahog or SP	1	1" x 3" x 7'
Deck Battens	Oak, Mahog or SP	2	1" x 2" x 4'
Strongback	Oak, Mahog or SP	1	1" x 3" x 6'
PLYWOOD:			
*Frame Gussets	DF Ext AB	1	3/8" x 4' x 4'
*Transom, Stem, Breasthook, Chine, Blocking & Knee	DF Ext AB	2	3/4" x 4' x 8'
Side Planking	DF Ext Mar AA or AB	2	3/8" x 3' x 18'**
Bottom Planking	DF Ext Mar AA or AB	2	3/8" x 3' x 16'**
Decking	DF Ext AB	2	3/8" x 4' x 8'
Floorboards, Seats, Bulkhead	DF Ext AB	3	3/8" x 4' x 8'
<p>*These items may be deleted if the frame kit has been purchased.</p> <p>**4' x 8' sheets can be substituted for longer sheets in all cases. Adjust quantities accordingly.</p>			

FASTENINGS:

Screws: Flathead wood type, bronze or hot dipped galvanized

- 1" #8 - 7 gross
- 1-1/4" #8 - 1 gross
- 2" #10 - 1 gross

Nails: Ring type boat nails, bronze or Monel

- 3/4" - 1 pound
- 1" - 2 pounds
- 1-1/4" - 3 pounds

Carriage Bolts: With nut and washer

- 5/16" x 6" - 6 required

Glue: Epoxy - 1 gallon