## **Huron Bill of Materials**

IN GENERAL: All lumber used should be free from shakes and knots. In the material listings mahogany and spruce are listed. Mahogany refers to the dark red variety and spruce to the sitka type. It is suggested that light weight materials be used whenever possible, Other lumbers not listed but of similar qualities may be substituted. All lumber listed as 3/4" is "four quarters" lumberyard material which when finished may vary, but commonly 3/4". ALL WIDTHS ARE NET. Lumber noted as 5/8" is to be NET; usually cut down from "four quarters" material.

All plywood must be of an exterior type. Douglas-fir (D.F.) plywood is considered satisfactory in all cases. Although long lengths may be used as noted in the text, the layouts noted are for standard 4' X 8' panels. Panel faces are designated as "A" or "B" faces or better, although a one side "C" veneer could be used on the deck. Douglas fir plywood is normally not available in thicknesses less than 1/4". For thinner plywood use the imported marine plywoods, measured in millimeters. These materials are more expensive; use when light weight is important. Use 1/4" material for economy.

Fastenings throughout should be either hot-dipped galvanized or bronze. For a boat of this type the galvanized can be considered to be completely adequate. All joints throughout the construction should be glued with a hard setting glue. Epoxy glue is recommended, but plastic resin glue can be used for economy except when gluing to oak or other woods that tend to react with this type of glue.

Abbreviations: DF = Douglas-fir, SP = Sitka spruce, MAH = Mahogany.

ITEM	MATERIAL	NO. PCs.	SIZE 13'/15'				
LUMBER:							
Keel	MAH or SP	1	3/4" x 1 1/2" x 12'/14'				
Knuckle	MAH or SP	2	3/4" x 1 1/4" x 14'/16'				
Chine logs	MAH or SP	2	5/8" x 1 1/4" x 14'/16'				
Inner sheer	MAH or SP	2	3/4" x 1" x 14'/16'				
Outer sheer	MAH or SP	2	3/4" x 1 1/4" x 14'/16'				
Center thwart	MAH or SP	1	3/4" x 6" x 3'				
End thwarts	MAH or SP	2	3/4" x 4" x 2'				
PLYWOOD							
Bottom planking/stems	AB Ext. DF	2	1/4" x 4' x 8'				
Lower side planking	AB Ext. DF	1	1/4" x 4' x 8'				

Upper side planking AB Ext. DF 1 1/4" x 4' x 8'					
	J	Upper side planking	AB Ext. DF	1	1/4" x 4' x 8'

**FASTENINGS** - Bronze or hot dipped galvanized:

**Screws** - Flat head, wood screws:

3/4" #8...6 gross 1" #8...1 gross

1 1/4" #8...1 gross

2" #8...4 only

Glue - EPOXY, plastic resin, or resorcinol

Half gallon, or 4 1/2 lbs. depending on type.