

Mist Miss Bill of Materials

The following list of materials is intended to be a general guide only. Before ordering any materials, the text and plans should be checked for possible options. All lumber listed as 1" stock is to be standard "lumberyard four-quarter" material which when finished may vary to somewhat less or slightly more than 3/4" in thickness. All widths are NET and all lengths allow for cutting to fit. Grouping lumber and purchasing random-random material to resaw to the required size will result in considerable savings. All lumber used should be first grade free from shakes and knots. Although oak (white oak), spruce (Sitka), and mahogany (dark red Philippine type) are called out in the listing, lumber typical to the locale and of similar types and weights may be substituted. All plywood (PW) is to be marine (MAR) or exterior (EXT) grade. The marine-type is preferable as the inner cores are solid and thus the panel has more structural integrity. Douglas-fir (DF) is satisfactory with the quality of the exposed faces of the veneer being designated by the letters "A" or "B". The "AA" grade panels are always preferable, however, "AB" grade is acceptable. All plywood should be a minimum of three plies. All fastenings should be bronze or hot dipped galvanized ferrous metal. Brass fastenings are not advised nor are the electroplated screws commonly sold in hardware stores. All screws are to be of the flat head type intended for wood. All nails are of the ring-type nail common to boat construction. Unless otherwise specified, all wood-to-wood joints are to be glued with a waterproof or highly water resistant glue such as plastic resin, resorcinol, epoxy, or other equivalent type used per the manufacturer's instructions regarding temperature, clamping requirements, curing time, and mixing method.

CHECK ALL SIZES TO THE WORK PRIOR TO CUTTING. Abbreviations used are: Mahog = mahogany; SP=Spruce; DF=Douglas-fir; PW=plywood; Ext=exterior; MAR=marine.

ITEM	MATERIAL	NO. PCS.	SIZE
LUMBER:			
Frame members*	Mahog or oak	75 Bd. Ft. of 1" stock	

Keel	Mahog or oak	1	1 1/4" x 4" x 13' 6"
Chines	Mahog or oak	2	1 1/8" x 2" x 18'
Sheers	Mahog or oak	4	5/8" x 1-1/4" x 20'
Battens	Mahog or oak	2 4	1" x 2" x 16' 1" x 2" x 14'
Motor stringers	DF or oak	2	2" x 6" x 13'
Carling	Mahog or oak	2	1" x 5" x 13'
Dash Board	Mahog	1	1" x 6" x 7'
Strongback	Mahog or SP	1	1" x 3" x 7'
Blocking	Mahog or SP	1" scrap as required	
Deck battens	Mahog or SP	2	1" x 2" x 6'
Coaming (optional)	Mahog	2	1" x 6" x 12'
Keel Strip (optional)	Oak	1	1" x 2" x 14'
Spray rail (optional)	Mahog or oak	2	3/4" x 1-1/4" x 18'
Bumper rail (optional)	Mahog or oak	2	1" x 3" x 6'6"

PLYWOOD:

Transom & frame gussets*	AB Ext	1	1/4" x 4' x 8'
Stem, breasthook, floor timbers*	AB Ext	1	3/4' x 4' x 8'
Planking-Bottom	MAR	2 4 OR 5	1/2" x 4' x 8' 1/4" x 4' x 10'** 1/4" x 4' x 8'
Planking-Side	MAR	2 OR 5	1/4" or 3/8" x 4' x 20'** 1/4" or 3/8" x 4' x 8'
Decking	AB Ext (see options)	2 1/2	3/8" x 4' x 8'

** 4' x 8' sheets can be substituted. Adjust quantities accordingly.

* These items are in the Frame Kit.

FASTENINGS:

- Screws: Flathead wood type, bronze or hot dipped galvanized
- 3/4"#8 - 5 doz
- 1 1/4" #8 - 5 gross
- 1 1/2" #8 - 1 gross
- 2" #10 - 1 gross 4 doz.
- 3" #14 - 2 doz
- Nails: Ring type boat nails, bronze or Monel
- 1"#12 - 2 lbs
- 1 1/4" - 1 1/2 lbs
- Carriage Bolts: Bronze or hot dipped galvanized complete with nuts and washers. Check lengths to work.
- 1/4"x2" - 40 each

- 5/16"x3" - 4 only
- 5/16"x5" - 3 only

Miscellaneous: Brass or iron angle 1/8"x1 1/4"x8" - 12 required (Optionally use wood blocking)

Glue: Epoxy - 1 gallon