

Pee Wee Bill of Materials

DO NOT PURCHASE ANY MATERIAL UNTIL YOU READ THIS SECTION.

LUMBER: All lumber listed as 1" is "Four quarters" stock finished as full as possible. This will generally result in lumber 3/4" to 7/8" thick. All thicknesses under 1" are to be considered net *as are all widths, unless noted otherwise*. All lengths allow stock for trimming to fit. We suggest grouping widths and lengths and re-sawing to size if a circular saw is available. This will result in a considerable savings on the lumber.

ALL **PLYWOOD** must be an Exterior type. Grades of plywood are noted. All plywood 3/16" or 1/4" thick is to be three ply. All thicker plywood to be a minimum of five ply.

CHECK ALL SIZES TO THE WORK PRIOR TO CUTTING. Abbreviations used are: Mahog = mahogany; Sp = spruce; DF = Douglas-fir; PW=plywood; Ext=exterior; Mar=Marine.

ITEM	MATERIAL	NO. PCS.	SIZE
Frames, dash, intermediate beams & skeg	Sp or Mahog	1 pc	1" x 8" (7-1/2" net) x 13'
Chine logs	Sp or Mahog	2 pcs.	5/8" x 1-1/2" x 8'
Sheer clamps	Sp or Mahog	4 pcs.	7/16" x 3/4" x 8'
Keel	Sp or Mahog	1 pc.	1" x 3" x 5'
Carling	Sp or Mahog	2 pcs.	1/2" x 2-1/2" x 5'
Strongback	Sp or Mahog	1 pc.	1/2" x 2" x 4'

Bottom Battens	Sp or Mahog	2 pcs.	1" x 1-1/2" x 5'
Transom, stem, knee, breasthook & #2 floor timber	Ext DF PW	1 pc.	3/4" x 3' x 4'
Planking	DF PW, Ext or Mar AB	1 pc. 1 pc.	3/16" or 1/4" x 3' x 8' 3/16" or 1/4" x 4' x 8'
Decking	DF or Mahog, Ext. PW	1 pc.	3/16" x 3' x 8'

FASTENINGS:

SCREWS: Flat head wood type, bronze or hot dipped galvanized.

- 3/4" #8 - 2 gross
- 1" #8 - 6 dozen
- 1" #8 - 7 dozen
- 1-1/4" #8 - 7 dozen
- 2" #10 - 5 only

NAILS: Annular thread type, bronze.

- 3/4" #15 - 1 lb.

CARRIAGE BOLTS: Hot dipped galvanized with nuts and washers. Check all lengths to work.

- 1/4" x 4" - 2 required
- 1/4" x 4-1/2" - 2 required
- 1/4" x 3" - 2 required

GLUE: Epoxy or plastic resin--Epoxy being preferable. 1 qt. or comparable volume.