

Picklefork Bill of Materials

DO NOT PURCHASE ANY MATERIAL UNTIL YOU READ THIS SECTION.

The following is the listing for all of the materials required for building the PICKLEFORK. Sitka Spruce is advocated for most wood working as it is extremely light in weight and yet very strong. Lumber in all cases is listed as actual thickness after milling. All widths are net, while all lengths allow cutting to fit. A considerable savings will result if the lumber is grouped and ripped to the proper widths from random stock. All plywood must be of an exterior grade. In most cases, an exterior grade with AB faces is specified. If the boat is to be used with the more powerful motors, or for rough useage, it is suggested that full solid core marine panels be used. Fir plywood is satisfactory in all cases, though for decking some may prefer to use mahogany or some other hardwood veneer faced panels. The Key# corresponds with the patterns.

CHECK ALL SIZES TO THE WORK PRIOR TO CUTTING. Abbreviations used are: Mahog = mahogany; SP = spruce; DF = Douglas-fir; PW=plywood; Ext=exterior; MAR=marine.

ITEM	MATERIAL	NO. PCS.	SIZE
LUMBER:			
#5, #6, #8, #15, #16, #17, #19, #26 and #9	SP or Mahog	100 Lin ft	3/4" x 3/4" (#9 to be ripped to thickness.)
Runner chines #10	SP or Mahog	2 pc.	5/8"x1-1/16"x5'
Bottom frames #21 & #23	SP or Mahog	2 pc.	3/4"x1-1/4"x3'
Frames #1, #2 and #3	SP	1 pc.	3/4"x7-1/2"x10'

Transom #28 frame & cap #20, #24 and #7 (see layout) Coaming #29 (see layout)	Mahog	1 pc.	3/4" x 6" x 5'
PLYWOOD:			
Bottom Planking #18 & runner bottom planking	DF Ext AB or	1 pc.	1/4" x 4' x 8'
#12 (see layout)	MAR AB PW	1 pc.	1/4" x 4' x 8'
#1, #4, #11, #13, #14, #20	DF Ext AB PW	2 pc.	1/4" x 4' x 8'
#22, #27, #31 and #32 (See Layout) #22, #25 & #28	DF Ext AB PW	1 pc.	1/2" x 4' x 4' (See Layout)
FASTENINGS:			
<ul style="list-style-type: none"> • Screws: Flathead wood type, bronze or hot dipped galvanized • 7/8" #8 - 4 gross • 1-1/4" #8 - 1 gross • 1-1/2" #8 - 6 dozen • Nails: Ring type boat nails, bronze or Monel • 3/4" - 1 pound • Carriage bolts with nut & washer: Hot dipped galvanized or Bronze • 1/4" x 5" - 2 required 			
Glue: Epoxy - 1 quart			