Renegade Bill of Materials

The following list of materials is intended to be a general guide only. Before ordering any materials, the text and plans should be checked for possible options. All lumber listed as 1" stock is to be standard "lumberyard four-quarter" material which when finished may vary to somewhat less or slightly more than 3/4" in thickness. All widths are NET and all lengths allow for cutting to fit. Grouping lumber and purchasing random-random material to resaw to the required size will result in considerable savings. All lumber used should be first grade free from shakes and knots. Although spruce (Sitka variety), oak (white oak), and mahogany (dark red Philippine type) are called out in the listing, lumber typical to the locale and of similar types and weights may be substituted. All plywood (PW) is to be marine (MAR) or exterior (EXT) grade. The marinetype is preferable as the inner cores are solid and thus the panel has more structural integrity. Douglas-fir (DF) is satisfactory with the quality of the exposed faces of the veneer being designated by the letters "A" or "B". The "AA" grade panels are always preferable, however, "AB" grade is acceptable. All plywood should be a minimum of three plies. All fastenings should be bronze or hot dipped galvanized ferrous metal. Brass fastenings are not advised nor are the electroplated screws commonly sold in hardware stores. All screws are to be of the flat head type intended for wood. All nails are of the ring-type nail common to boat construction. Unless otherwise specified, all wood-to-wood joints are to be glued with a waterproof or highly water resistant glue such as plastic resin, resorcinol, epoxy, or other equivalent type used per the manufacturer's instructions regarding temperature, clamping requirements, curing time, and mixing method.

CHECK ALL SIZES TO THE WORK PRIOR TO CUTTING. Abbreviations used are: Mahog = mahogany; SP=Spruce; DF = Douglas-fir; PW=plywood; Ext=exterior; MAR=marine.

ITEM	MATERIAL	NO. PCS.	SIZE
LUMBER:			

Frame members/deck beams	Mahog, Oak or Sp	75 bd. ft. Random-random four quarters stock, with some widths to 7". 12 bd ft of 1-1/4" (five quarters) stock for transom frames	
Keel-jetdrive version	Mahog, Oak or SP	1 1	2" x 4" x 10' 2" x 12" x 5'
Keel-other versions	Mahog, Oak or SP	1	2" x 4" x 13'
Chine logs	Mahog, Oak or SP	2	1-1/4" x 2-1/4" x 20'
Sheer clamps	Mahog, Oak or SP	4	3/4" net x 1-1/2" x 22'
Sheer clamp inner lams	Mahog, Oak or SP	1	3/4" net x 1-1/2" x 12'
Bottom Battens	Mahog, Oak or SP	2 2 2 2 2	1" x 2-1/2" x 18' 1" x 2-1/2" x 17' 1" x 2-1/2" x 14' 1" x 2-1/2" x 12'
Set-up stringers	Mahog, DF or SP	2	2" x 6" x 12'*
Motor stringers uprights (inb)	Mahog, DF or Oak	2	2" x 4" x 2'*
Motor stringer blocking (inb)	Mahog, DF or Oak	1	2" x 2" x 10'*

Motor well beam (outboards)	Mahog, DF or Oak	1	2" x 4" x 3'		
Motor well side uprights (outbd)	Mahog, DF or Oak	2	2" x 2" x 2'		
Decking strongback	Mahog, Oak or SP	1	1" x 2" x 10'		
Deck battens	Mahog, Oak or SP	2 2	1" x 2" x 9' 1" x 2" x 8'		
Carling	Mahog, Oak or SP	2	1" x 6" x 15'		
Coaming	Mahog	2	1" x 7" x 15'		
Filler blocking	Mahog, Oak or SP	2	1" x 2" x 8'		
Lift strakes	Mahog	2 2	1" x 3" x 14' 1" x 3" x 12'		
*Designates standard lumberyard size in both width and thickness.					
PLYWOOD:					
Side planking	DF Mar AB or AA	2 2	3/8" x 4' x 10'** 3/8" x 4' x 12'**		
Bottom planking	DF Mar AB or AA	2 4	1/2" x 4' x 8' 1/4" x 4' x 12'**		

Decking & butt blocks	DF Ext AB or Mahog PW	4	3/8" x 4' x 8'
Inner keel laminations & motor stringer laminations	DF Ext AB	1	3/8" x 4' x 8'
Gussets	DF Ext AB	1	1/4" x 4' x 4'
Transom, floor timbers & transom knee	DF Ext AB	1	3/4" x 4' x 8'
Stem & breasthook lams	DF Ext AB	1	3/4" x 4' x 8'
Cockpit sole & bottom planking butt blocks	DF Ext AC	1	1/2" x 4' x 8'
Motor well structure (outbds)	DF Ext AB	2	1/2" x 4' x 8'
Motor well bulkhead (outbds)	DF Ext AB	1	3/8" x 2' x 8'

^{**4&#}x27; x 8' sheets can be substituted for longer sheets in all cases. Adjust quantities accordingly.

FASTENINGS:

Screws: Flathead wood type, bronze or hot dipped galvanized

- 3/4" #8 1 gross
- 1" #8 8 gross
- 1-1/4" #8 6 gross
- 1-1/2" #8 3 gross
- 2" #10 1 gross
- 3" #14 6 dozen

Nails: Ring type boat nails, bronze or Monel

- 1" 2 pounds
- 1-1/4" 1 pound

Glue: Epoxy - 1 gallon