Super Spartan Bill of Materials

DO NOT PURCHASE ANY MATERIAL UNTIL YOU READ THIS SECTION. The following is the listing for all of the materials required for building the SUPER SPARTAN. Sitka Spruce is advocated for most wood working as it is extremely light in weight and yet very strong. Lumber in all cases is listed as actual thickness after milling. All widths are net, while all lengths allow cutting to fit. A considerable savings will result if the lumber is grouped and ripped to the proper widths from random stock. All plywood must be of an exterior grade. In most cases, an exterior grade with AB faces is specified. If the boat is to be used with the more powerful motors, or for rough useage, it is suggested that full solid core marine panels be used. Fir plywood is satisfactory in all cases, though for decking some may prefer to use mahogany or some other hardwood veneer faced panels.

CHECK ALL SIZES TO THE WORK PRIOR TO CUTTING. Abbreviations used are: Mahog = mahogany; Sp = spruce; DF = Douglas-fir; PW=plywood; Ext=exterior.

ITEM	MATERIAL	NO. PCS.	SIZE		
LUMBER:					
Runner Chines**, Transom & #2 Frame**	Spruce or Mahog	1	3/4" x 6" x 12'		
Strongback**, Frames #1 & 3**, Non-trip Chines	Spruce or Mahog	1	1/2" x 6" x 11'		
Bottom Battens & Chine	Spruce or Mahog	5	3/4" x 2" x 8'		
Sheer Clamps & Carling	Spruce or Mahog	4	3/4" x 1" x 10'		
Deck Batten	Spruce or Mahog	2	1/2" x 1" x 7'		

	og 2	1/2" x 8" x 11'
Knee DF (Lur	nberyard size)	2" x 6" x 2'

PLYWOOD:

Bottom Planking, Frame Gussets-Bow Pc.**	DF PW Ext AB	1	1/4" x 4' x 8'
Runner, Side, Non-trip Planking & Butt Blk	DF PW Ext AB	1	1/4" x 4' x 8'
Transom**, Dash Beam** Bow Pieces**	DF PW Ext AB	1	1/2" x 4' x 8'
Decking	DF PW Ext AB	2	1/8" x 4' x 8'

^{**}In Frame Kit

FASTENINGS:

Screws: Flathead wood type, bronze or hot dipped galvanized

- 1-1/2" #8 4 dozen
- 3" #14 4 each

Nails: Ring type boat nails, bronze or Monel

- 3/4" 2 pounds
- 1 1/4" 3/4 pound

Glue: Epoxy - 1 quart