

Tiny Might Bill of Materials

The following list of materials is intended to be a general guide only. Before ordering any materials, the text and plans should be checked for possible options. All lumber listed as 1" stock is to be standard "lumberyard four-quarter" material which when finished may vary to somewhat less or slightly more than 3/4" in thickness. All widths are NET and all lengths allow for cutting to fit. Grouping lumber and purchasing random-random material to resaw to the required size will result in considerable savings. All lumber used should be first grade free from shakes and knots. Although oak (white oak), spruce (Sitka), and mahogany (dark red Philippine type) are called out in the listing, lumber typical to the locale and of similar types and weights may be substituted. All plywood (PW) is to be marine (MAR) or exterior (EXT) grade. The marine-type is preferable as the inner cores are solid and thus the panel has more structural integrity. Douglas-fir (DF) is satisfactory with the quality of the exposed faces of the veneer being designated by the letters "A" or "B". The "AA" grade panels are always preferable, however, "AB" grade is acceptable. All plywood should be a minimum of three plies. All fastenings should be bronze or hot dipped galvanized ferrous metal. Brass fastenings are not advised nor are the electroplated screws commonly sold in hardware stores. All screws are to be of the flat head type intended for wood. All nails are of the ring-type nail common to boat construction. Unless otherwise specified, all wood-to-wood joints are to be glued with a waterproof or highly water resistant glue such as plastic resin, resorcinol, epoxy, or other equivalent type used per the manufacturer's instructions regarding temperature, clamping requirements, curing time, and mixing method.

CHECK ALL SIZES TO THE WORK PRIOR TO CUTTING.

Abbreviations used are: Mahog = mahogany; SP = Spruce; DF = Douglas-fir; PW=plywood; Ext=exterior; MAR=marine.

ITEM	MATERIAL	NO. PCS.	SIZE
LUMBER:			
Frames	SP or Mahog	30 Random-random bd ft. 1" material	
Motor Stringers	SP or Mahog	2	1" x 6" 10'

Keel	SP or Mahog	1	1" x 4" x 9'
Battens	SP or Mahog	4	1" x 1-1/2" x 9'
Sheer Clamp	SP or Mahog	4	1" x 1-1/2" x 14'*
Chine Log	SP or Mahog	2	1" x 1-1/2" x 13'
Carling	Mahog	2	1" x 3" x 9'*
Coaming	Mahog	2	1" x 9" x 6'***
Beams & Hatch Frames	SP or Mahog	1	1" x 4" x 16'*
Strongback	SP or Mahog	1	1" x 2" x 11'
Deck Battens	SP or Mahog	2	1" x 1-1/2" x 5'*
Seat Back Brace	SP or Mahog	2	1" x 1-1/2" x 18"

* Can substitute 5/8" material to save weight.

** Can substitute 1/2" material to save weight.

PLYWOOD:

Transom	PW DF AB	1	3/8" x 2' x 5'
Side Planking	PW DF AB Marine	2 OR 1	1/4" x 4' x 8' 4'x14' if avail.
Bottom Planking	PW DF AB Marine	3 OR 2	1/4" or 3/8" x 4' x 8' 4'x12' if avail.
Stem	PW DF AB	1	3/4" x 2' x 5'
Gussets & Laminations	PW DF AB	1	1/4" x 4' x 8'
Decking	PW Mahog, or D.F. AB	2	1/4" or 1/8" x 4' x 8'

FASTENINGS:

Screws: Flathead wood type, bronze or hot dipped galvanized

- 3/4" #8 - 1 gross
- 1"#8 - 4 gross
- 1 1/2" #8 - 1 gross
- 2" #10 - 14 only

Nails: Ring type boat nails, bronze or Monel

- 1" - 3 pounds

Carriage Bolts: Bronze or hot dipped galvanized complete with nuts and washers. Check lengths to work.

- 1/4" - 2 required (keel to stem)

Glue: Epoxy - 1 gallon

